

GRANFILL

Gel filler for mixing with sanding dust



GRANWAX
Limited

Installation, Finishing & Maintenance Systems
for Wood and Sports Floors

DESCRIPTION

Granwax Granfill is designed to be mixed with the sanding dust from the final sanding of the wood floor ensuring an accurate colour match when filling gaps, cracks and joints. Preferably, use the sanding dust generated from using 120 grit or finer sandpaper to achieve best results. Ideal for overcoating with any of the Granwax range of finishes.

Please note: **Granwax Granfill** is not suitable for filling gaps between floorboards which are hollow beneath.



PREPARATION

The surface to be treated must be completely dry. Apply in dry, non humid conditions and at room temperature.



THE PRODUCT

- ✓ Available sizes: 5 litres & 1 litre
- ✓ Spirit based gel filler for mixing with sanding dust
- ✓ Fast drying
- ✓ Flexible
- ✓ No shrinkage

PROUDLY MADE IN THE UK





TECHNICAL INFORMATION

DRYING TIME

Touch dry in 30-60 minutes, dependent on site conditions. Please note that poor ventilation, low temperature and/or high humidity will extend or affect product drying and curing.

STORAGE

Avoid storing in extreme hot or cold temperatures. Ideally, store between 10°C and 30°C. Protect from frost.

SHELF LIFE

Please refer to 'Use by' date on top of container. For best results, opened containers should be used immediately.

HEALTH & SAFETY

For product health and safety information, please refer to our Material Safety Data Sheet.

**Please note that drying times will be extended or reduced dependent on site conditions. In some circumstances this may affect the overall appearance if not properly addressed.*

The information provided herein is correct to the best of our knowledge. No liability for any errors or omissions is accepted. Granwax Products Ltd can accept no responsibility or liability for any loss as a result of any person placing reliance on any information contained herein nor for any loss or damage arising from the use of this product if used in areas subjected to severe abrasion, i.e. broken glass or impact damage. Prospective users should therefore satisfy themselves by appropriate trials that the product is suitable for the intended purpose.

This revision August 2024.

APPLICATION

Please note that **Granwax Granfill** is very fast drying so during application it will be necessary to add further resin to the mix to maintain a workable paste texture for correct and effective filling.

Mix enough **Granwax Granfill** with the final fine sanding dust to make a smooth textured paste. Using a flat blade trowel, apply the filler to the entire floor or preferred application, ensuring that the filler penetrates and fills the gaps to maximum. Allow to dry completely before assessing whether another application will be required to ensure the gaps are filled. Once completed, sand off the excess filler prior to applying your desired Granwax finish to the floor.



GRANWAX
Limited



Part of the ISF Group Limited

West Street • Riddings • Alfreton • Derbyshire • DE55 4EW

Telephone: 01773 541177 • Email: info@granwax.com • www.granwax.com

Installation, Finishing & Maintenance Systems for Wood and Sports Floors