

eZee WOOD FLOOR POLISH



GRANWAX
Limited

Installation, Finishing & Maintenance Systems
for Wood and Sports Floors

Semi-buffable, fast drying emulsion polish

DESCRIPTION

Granwax Ezee Wood Floor Polish is a semi-buffable, fast drying emulsion polish. Sheen level can be increased by burnishing if required. Offers a very good durable finish, designed to combat scuff marking. **Granwax Ezee Wood Floor Polish** is ideal for use on sealed/coated wood and cork surfaces, thermoplastic, linoleum, vinyl and asphalt. Do not use polish on floors used for any type of sporting activities.



PREPARATION

Clean the floor thoroughly, removing any old dressings or polish with your preferred Granwax stripper product, **Granwax Lift Off** or **Granwax Swift**, diluted with warm water. If this procedure is carried out on a wood floor surface, care is needed as the use of alkaline based strippers will damage unsealed/coated timber. To neutralise the surface, rinse with **Granwax Neutrasol** at correct dilution rate and finally rinse again with clean water. Allow floor to dry.



THE PRODUCT

- ✓ Available sizes: 5 litres & 1 litre
- ✓ Ready to use
- ✓ Fast drying
- ✓ Satin finish
- ✓ Enhances the natural beauty of the wood

PROUDLY MADE IN THE UK





APPLICATION

Ensure floor surface is clean and thoroughly dry before application. Some sealed/coated surfaces may need to be lightly abraded to form a 'key' for polish to adhere. Apply a thin, even coat of **Granwax Ezee Wood Floor Polish** by applicator, clean mop or, for larger floor areas a Granwax applicator can be used. It is recommended that the first coat of polish is kept approximately 6 inches away from outer edge of the floor to prevent build-ups. Do not rub into floor. When first coat is dry, apply second coat at right angles to the first, this time ensuring all floor surface is covered. The polish film will harden for several hours after drying, therefore, for best results, the floor should be left as long as possible before use, preferably overnight.

SHEEN LEVELS



TECHNICAL INFORMATION

COVERAGE

40-50m² per litre (200-300m² per 5 litre). This coverage rate is offered as a guide only. Pack sizes are 5 litre and 750 millilitres.

STORAGE

Store in a cool, dry place. Protect from frost. Keep out of the reach of children.

SHELF LIFE

Please refer to 'Use by' date on top of container. For best results, opened containers should be used immediately.

MAINTENANCE

When cured (minimum 5 days) a maintenance programme can be implemented. Floor maintenance specifications are available on our website, or contact us, our local representative or supplier.

HEALTH & SAFETY

For product health and safety information, please refer to our Material Safety Data Sheet.

The information provided herein is correct to the best of our knowledge. No liability for any errors or omissions is accepted. You should satisfy yourself by appropriate trials that the product is suitable for the intended use. Granwax Limited can accept no responsibility for any loss as a result of any person placing reliance on any material contained herein.

This revision August 2024.



GRANWAX
Limited



Part of the ISF Group Limited

West Street • Riddings • Alfreton • Derbyshire • DE55 4EW

Telephone: 01773 541177 • Email: info@granwax.com • www.granwax.com

Installation, Finishing & Maintenance Systems for Wood and Sports Floors